BONDING BLOCK Platinum Series With DSM® Seizure PCT-GB-1P



Innovation for the Last Mile



SUPERIOR CRITICAL CATEGORY PERFORMANCE

ELIMINATES FAILURE POTENTIAL



UNIQUE FEATURES

PCT's Platinum Series Bonding Block is engineered to eliminate the potential for failure, and offer superior performance in all critical categories:

- ✓ One-piece splice and body eliminates corrosion between multi-component body construction.
- ✓ High quality, corrosion resistant extruded aluminum alloy
- ✓ Machined brass F-81 connectors
- ✓ PCT's patented DSM seizure for superior center conductor retention, reduced common path distortion, and excellent electrical performance (including min. -30 dB return loss thru 1 GHz).

ADVANCED FEATURES

- Gold plated beryllium copper seizure has ideal electrical and mechanical characteristics, with exceptional spring back and center conductor retention that does not require assistance from a plastic insulator
- 100% conformance to SCTE standards for center conductor retention without any assistance from plastic insulators that relax over time
- High quality, corrosion resistant extruded aluminum alloy
- Precision machined SCTE conforming ports for superior F-connector performance
- Includes grounding wire screw and two mounting screws

GENERAL SPECIFICATIONS

Bandwidth 5 MHz to 3 GHz Impedance 75 Ohms (nominal)
Return Loss Minimum -25 dB to 3 GHz

Shielding Effectiveness -100 dB minimumInsertion Loss $\leq .5 \text{dB} \otimes 3 \text{GHz}$

Operating Temperature -40 to +140 °F (-40 to +60 °C)Ground Wire Gauge Accepts up to #6 ground wire

Ordering Information

PCT-GB-1P Ground Block, Platinum Series with DSM Seizure

