

APA1260315URH

Power Adapter, Wall Mount Linear, Type "A" Plug, 15 V 0.3 A

APA1260315URH

Input Requirements

Parameter	Typical Values
Input Voltage	120 VAC
Frequency	60 Hz

Output Features

Parameter	Limit			Test Conditions
	Min	Typ	Max	
Output Voltage	--	--	24.5 VDC	0 A Loading
Output Voltage	14.25 VDC	15.0 VDC	15.75 VDC	0.5 A Loading
Output Load	0 A	--	0.5 A	--
Ripple & Noise	--	--	1.5 Vp-p	--
Efficiency	--	CEC IV	--	--

Environmental Conditions

Parameter	Values
Operating Conditions	-14 to 122 °F (-10 to 55 °C) 30 to 90 % Relative Humidity
Storage Temperature	-40 to 149 °F (-40 to 65 °C)

Reliability & Safety

Parameter	Values
Safety	UL / CUL 60065
Insulation System	Class B (130°)
Dielectric Strength (Hi-Pot)	Shall withstand without breakdown 2 KV 60 Hz for one (1) minute between blades and output plug and case
Surge Withstand	IEEE C62.41-1991 Category B-3 Combination Wave, 6kV, 3kA, on the 120 VAC input per ANSI / SCTE 81 2012
Standards Conformance	ANSI / SCTE 161 2009

Ordering Information

Part Number	Description
APA1260315URH	Power Supply, Wall Mount Linear, Type "A" Plug, 15 V 0.5 A

